



RemOx® S-F ISCO Reagent

EC- SAFETY DATA SHEET according to Regulation (EC) № 1907/2006 of the European Parliament and of the Council, of 18 December 2006 concerning REACH

Material Safety Data Sheet
Page 1 of 9

Section 1 Chemical Product and Company Identification

PRODUCT NAME: RemOx® S-F ISCO Reagent TRADE NAME: RemOx® S-F ISCO Reagent		Revised Date: May 2008
USES OF SUBSTANCE: RemOx® S-F ISCO Reagent is an oxidant recommended for applications that require a strong oxidant.		
COMPANY NAME (Europe): CARUS NALON S.L.	COMPANY ADDRESS: Carus Nalon S.L. Barrio Nalon, s/n 33100 Trubia-Oviedo Espana, Spain	INFORMATION: (34) 985-785-513 (34) 985-785-513 www.caruseurope.com (Web) carus@carusnalon.com (Email)
COMPANY NAME (US): CARUS CORPORATION	COMPANY ADDRESS: 315 Fifth Street Peru, IL 61354, USA	EMERGENCY TELEPHONE: (34) 985-785-513
	INFORMATION: (815)-223-1500 www.caruscorporation.com (Web) salesmkt@caruscorporation.com (Email)	EMERGENCY TELEPHONE: (800) 435 -6856 (USA) (800) 424-9300 (CHEMTREC, USA) (815-223-1500 (Other countries)

Section 2 Hazards Identification

<p>1. <u>EYE CONTACT</u> RemOx® S-F ISCO Reagent is damaging to eye tissue on contact. It may cause severe burns that result in damage to the eye.</p> <p>2. <u>SKIN CONTACT</u> Contact of solutions at room temperature may be irritating to the skin, leaving brown stains. Concentrated solutions at elevated temperature and crystals are damaging to the skin.</p> <p>3. <u>INHALATION</u> Acute inhalation toxicity data are not available. However, airborne concentrations of RemOx® S-F ISCO Reagent the form of dust or mist may cause damage to the respiratory tract.</p> <p>4. <u>INGESTION</u> RemOx® S-F ISCO Reagent , if swallowed, may cause severe burns to mucous membranes of the mouth, throat, esophagus, and stomach.</p>
--



RemOx® S-F ISCO Reagent

EC- SAFETY DATA SHEET according to Regulation (EC) № 1907/2006 of the European Parliament and of the Council, of 18 December 2006 concerning REACH

Material Safety Data Sheet
Page 2 of 9

Section 3 Hazardous Ingredients

<u>MATERIAL OR COMPONENT</u>	<u>CAS NO.</u>	<u>EINECS</u>	<u>HAZARD DATA</u>
Potassium Permanganate	7722-64-7	231-760-3	PEL/C 5 mg Mn per cubic meter of air TLV-TWA 0.2 mg Mn per cubic meter of air
Silicon Dioxide	112926-00-8		
<u>HAZARD SYMBOLS:</u>			
<u>RISK PHRASES:</u>			
8	Contact with combustibles may cause fire.		
22	Harmful if swallowed.		
50/53	Very toxic to aquatic organisms, may cause long-term effects in the aquatic environment.		
<u>SAFETY PHRASES:</u>			
60	This material and its container must be disposed of as hazardous waste.		
61	Avoid releases to the environment. Refer to special instructions / Safety data sheet.		

Section 4 First Aid Measures

1. EYES

Immediately flush eyes with large amounts of water for at least 15 minutes holding lids apart to ensure flushing of the entire surface. Do not attempt to neutralize chemically. Seek medical attention immediately.

Note to physician: Soluble decomposition products are alkaline. Insoluble decomposition product is brown manganese dioxide.

2. SKIN

Immediately wash contaminated areas with water. Remove contaminated clothing and footwear. Wash clothing and decontaminate footwear before reuse. Seek medical attention immediately if irritation is severe or persistent.

3. INHALATION

Remove person from contaminated area to fresh air. If breathing has stopped, resuscitate and administer oxygen if readily available. Seek medical attention immediately.

4. INGESTION

Never give anything by mouth to an unconscious or convulsing person. If person is conscious, give large quantities of water. Seek medical attention immediately.



RemOx® S-F ISCO Reagent

EC- SAFETY DATA SHEET according to Regulation (EC) № 1907/2006 of the European Parliament and of the Council, of 18 December 2006 concerning REACH

Material Safety Data Sheet
Page 3 of 9

Section 5 Fire Fighting Measures

NFPA* HAZARD SIGNS

Health Hazard	1	=	Materials which under fire conditions would give off irritating combustion products. (less than 1 hour exposure) Materials that on the skin could cause irritation.
Flammability Hazard	0	=	Materials that will not burn.
Reactivity Hazard	0	=	Materials which in themselves are normally stable, even under fire exposure conditions, and which are not reactive with water.
Special Hazard	OX	=	Oxidizer

*National Fire Protection Association 704 (USA)

FIRST RESPONDERS:

Wear protective gloves, boots, goggles, and respirator. In case of fire, wear positive pressure breathing apparatus. Approach incident with caution.

FLASHPOINT

None

FLAMMABLE OR EXPLOSIVE LIMITS

Lower: Nonflammable Upper: Nonflammable

EXTINGUISHING MEDIA

Use large quantities of water. Water will turn pink to purple if in contact with RemOx® S-F ISCO Reagent. Dike to contain. Do not use dry chemicals, CO₂ Halon® or foams.

SPECIAL FIREFIGHTING PROCEDURES

If material is involved in fire, flood with water. Cool all affected containers with large quantities of water. Apply water from as

far

a distance as possible. Wear self-contained breathing apparatus and full protective clothing.

UNUSUAL FIRE AND EXPLOSION

Powerful oxidizing material. May decompose spontaneously

if

exposed to heat (150°C / 302°F). May be explosive in contact with certain other chemicals (Section 10). May react violently with finely divided and readily oxidizable substances. Increases burning rate of combustible material.

Section 6 Accidental Release Measures

PERSONAL PRECAUTIONS:

Ensure adequate ventilation. Avoid dust formation. Avoid inhalation and contact with eyes and skin. Personnel should wear protective clothing suitable for the task. Remove all ignition sources and incompatible materials before attempting clean up.

ENVIRONMENTAL PRECAUTIONS:

Do not flush into sanitary sewer system or surface water. If accidental release into the environment occurs, inform the responsible authorities. Keep the product away from drains, sewers, surface and ground water and soil.

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Clean up spills immediately by sweeping or shoveling up the material. Do not return spilled material to the original container – transfer to a clean metal drum. To clean contaminated surfaces or floors, flush with abundant quantities of water into sewer, if permitted by federal, state, and local regulations - if not, collect water and treat chemically (Section 13).



RemOx® S-F ISCO Reagent

EC- SAFETY DATA SHEET according to Regulation (EC) № 1907/2006 of the European Parliament and of the Council, of 18 December 2006 concerning REACH

Material Safety Data Sheet
Page 4 of 9

Section 7 Handling and Storage

WORK/HYGIENIC PRACTICES

Wash hands thoroughly with soap and water after handling RemOx S -F ISCO Reagent. Do not eat, drink or smoke when working with RemOx® S-F ISCO Reagent. Wear proper protective equipment. Remove clothing, if it becomes contaminated.

VENTILATION REQUIREMENTS

Provide sufficient mechanical and/or local exhaust to maintain exposure below the TLV/TWA.

CONDITIONS FOR SAFE STORAGE

Store in accordance with NFPA 430 requirements for Class II oxidizers. Protect containers from physical damage. Store in a cool, dry area in closed containers. Segregate from acids, peroxides, formaldehyde, and all combustible, organic, or easily oxidizable materials including antifreeze and hydraulic fluid.

Section 8 Exposure Controls and Personal Protection

RESPIRATORY PROTECTION

In cases where overexposure to dust may occur, the use of an approved NIOSH-MSHA dust respirator or an air supplied respirator is advised. Engineering or administrative controls should be implemented to control dust

EYE

Faceshield, goggles, or safety glasses with side shields should be worn. Provide eyewash in working area.

GLOVES

Rubber or plastic gloves should be worn.

OTHER PROTECTIVE EQUIPMENT

Normal work clothing covering arms and legs, and rubber, or plastic apron should be worn.

Section 9 Physical and Chemical Properties

APPEARANCE AND ODOR	Dark purple solid with metallic luster, odorless
BOILING POINT, 760 mm Hg	Not applicable
VAPOR PRESSURE (mm Hg)	Not applicable
SOLUBILITY IN WATER % BY SOLUTION	6% at 20°C (68°F) and 20% at 65°C (149°F)
PERCENT VOLATILE BY VOLUME	Not volatile
EVAPORATION RATE	Not applicable
MELTING POINT	Starts to decompose with evolution of oxygen (O ₂) at temperatures above 150°C (302°F). Once initiated, the decomposition is exothermic and self-sustaining.
SPECIFIC GRAVITY	2.7 at 20°C (68°F)
BULK DENSITY	Approximately 1.45 - 1.6 kg / l
VAPOR DENSITY (AIR=1)	Not applicable
OXIDIZING PROPERTIES	Strong oxidizer



RemOx® S-F ISCO Reagent

EC- SAFETY DATA SHEET according to Regulation (EC) № 1907/2006 of the European Parliament and of the Council, of 18 December 2006 concerning REACH

Material Safety Data Sheet
Page 5 of 9

Section 10 Stability and Reactivity

STABILITY	Under normal conditions, the material is stable.
CONDITIONS TO AVOID	Contact with incompatible materials or heat (150°C / 302°F) could result in violent exothermic chemical reaction.
INCOMPATIBLE MATERIALS	Acids, peroxides, formaldehyde, anti-freeze, hydraulic fluids and all combustible organic or readily oxidizable inorganic materials including metal powders. With hydrochloric acid, chlorine gas is liberated.
HAZARDOUS DECOMPOSITION PRODUCTS	When involved in a fire, RemOx® S-F ISCO Reagent may liberate corrosive fumes.
CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION	Material is not known to polymerize.

Section 11 Toxicological Information

POTASSIUM PERMANGANATE:

1. ACUTE TOXICITY

INGESTION:

LD 50 oral rat: 780 mg/kg male (14 days); 525 mg/kg female (14 days).

Harmful if swallowed. ALD: 10g. Ingestion may cause nausea, vomiting, sore throat, stomach-ache and eventually lead to a perforation of the intestine. Liver and kidney injuries may occur.

SKIN CONTACT:

LD 50 dermal no data available.

The product may be absorbed into the body through the skin. Major effects of exposure: severe irritation, brown staining of skin.

INHALATION:

LC 50 inhalation: No data available.

The product may be absorbed into the body by inhalation. Major effects of exposure: respiratory disorder, cough.

2. CHRONIC TOXICITY

No known cases of chronic poisoning due to permanganates have been reported. Prolonged exposure, usually over many years, to heavy concentrations of manganese oxides in the form of dust and fumes may lead to chronic manganese poisoning, chiefly involving the central nervous system.

3. CARCINOGENICITY

Potassium permanganate has not been classified as a carcinogen by ACGIH, NIOSH, OSHA, NTP, or IARC.

4. MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Potassium permanganate solution will cause further irritation of tissue, open wounds, burns or mucous membranes.



RemOx® S-F ISCO Reagent

EC- SAFETY DATA SHEET according to Regulation (EC) № 1907/2006 of the European Parliament and of the Council, of 18 December 2006 concerning REACH

Material Safety Data Sheet
Page 6 of 9

Section 12 Ecological Information

ENTRY TO THE ENVIRONMENT

Potassium permanganate has a low estimated lifetime in the environment, being readily converted by oxidizable materials to insoluble MnO₂.

BIOCONCENTRATION POTENTIAL

In non-reducing and non-acidic environments, MnO₂ is insoluble and has a very low bioaccumulative potential.

AQUATIC TOXICITY

The toxicity data for Potassium permanganate is given below:

Rainbow trout, 96 hour LC ₅₀ :	1.8 mg/L
Bluegill sunfish, 96 hour LC ₅₀ :	2.3 mg/L
Milk fish (Chanos Chanos)/ 96 hour LC ₅₀ :	>1.4mg/l

Section 13 Disposal Considerations

Offer surplus and non-recyclable product or solutions to a licensed disposal company.

Reduce RemOx® S-F ISCO Reagent in aqueous solutions with sodium thiosulfate, a bisulfite or ferrous salt solution. The bisulfite or ferrous salt may require some dilute sulfuric acid (10% w/w) to promote reduction. Neutralize with sodium carbonate to neutral pH, if acid was used. Decant or filter and deposit sludge in approved landfill. Where permitted, the sludge may be drained into sewer with large quantities of water. Contact Carus Chemical Company for additional recommendations.

Packaging materials must be triple rinsed to remove all RemOx S-F ISCO Reagent prior to re-cycling or disposal.

Section 14 Transport Information

USA (land, D.O.T.)	Proper Shipping Name: 49 CFR172.101....Potassium Permanganate Hazard Class: 49 CFR172.101....Oxidizer ID Number: 49 CFR172.101....UN 1490 Packing Group: 49 CFR172.101....II Division: 49 CFR172.101....5.1
European Labeling in accordance Road/Rail Transport (ADR/RID)	ID Number: UN 1490 ADR/RID Class 5.1 Description of Goods: Potassium Permanganate Hazard Identification No. 50
European Labeling in accordance with EC directive (Water, I.M.O.)	Proper Shipping Name: Potassium Permanganate Hazard Class: Oxidizer ID Number: UN 1490 Packing Group: II Division: 5.1 Marine Pollutant: No



RemOx® S-F ISCO Reagent

EC- SAFETY DATA SHEET according to Regulation (EC) № 1907/2006 of the European Parliament and of the Council, of 18 December 2006 concerning REACH

Material Safety Data Sheet
Page 7 of 9

Section 14 Transport Information (contd.)

European Labeling in accordance with EC directive (Air, I.C.A.O.)	Proper Shipping Name:	Potassium Permanganate
	Hazard Class:	Oxidizer
	ID Number:	UN 1490
	Packing Group:	II
	Division:	5.1

Section 15 Regulatory Information

EUROPEAN AND INTERNATIONAL REGULATIONS:

MARKINGS ACCORDING TO EU GUIDELINES:

The product has been classified and marked in accordance with EU directives/ordinances on hazardous materials.

CHEMICAL NAME

Potassium Permanganate

CAS NO.

7722-64-7

EINECS

231-760-3

UN NUMBER

UN 1490

CODE LETTER AND HAZARD DESIGNATION OF THE PRODUCT:



O
Oxidizer



Xn
Harmful



N
Dangerous to the Environment

RISK PHRASES:

- 8 Contact with combustibles may cause fire.
- 22 Harmful if swallowed.
- 50/53 Very toxic to aquatic organisms, may cause long-term effects in the aquatic environment.

SAFETY PHRASES:

- 60 This material and its container must be disposed of as hazardous waste.
- 61 Avoid releases to the environment. Refer to special instructions / Safety data sheet.



RemOx® S-F ISCO Reagent

EC- SAFETY DATA SHEET according to Regulation (EC) № 1907/2006 of the European Parliament and of the Council, of 18 December 2006 concerning REACH

Material Safety Data Sheet
Page 8 of 9

Section 15 Regulatory Information (contd.)

US FEDERAL REGULATIONS:

CHEMICAL INVENTORY STATUS – PART 1

<u>Ingredient</u>	<u>CAS. NO.</u>	<u>TSCA</u>	<u>EC</u>	<u>Japan</u>	<u>Australia</u>
Potassium Permanganate	7722-64-7	Yes	Yes		

CHEMICAL INVENTORY STATUS – PART 2 --- CANADA---

<u>Ingredient</u>	<u>CAS. NO.</u>	<u>Korea</u>	<u>DSL</u>	<u>NDSL</u>	<u>PHIL</u>
Potassium Permanganate	7722-64-7	No	Yes		

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulation (CPR, Canada) and the MSDS contains all of the information required by the CPR.

FEDERAL, STATE & INTERNATIONAL REGULATIONS – PART 1

<u>Ingredient</u>	<u>CAS. NO.</u>	<u>SARA 302</u>		<u>SARA 313</u>	
		<u>RQ</u>	<u>TPQ</u>	<u>List</u>	<u>Chemical Catg.</u>
Potassium Permanganate	7722-64-7	N/A	N/A	Yes	Yes

(Manganese compounds)

FEDERAL, STATE & INTERNATIONAL REGULATIONS – PART 2

<u>Ingredient</u>	<u>CAS. NO.</u>	<u>CERCLA</u>	<u>RCRA</u>	<u>TSCA 8(d)</u>
Potassium Permanganate	7722-64-7	Yes (RQ =100 lbs)	D001	No

<u>Ingredient</u>	<u>CAS. NO.</u>	<u>CWC</u>	<u>TSCA 12(b)</u>	<u>CDTA</u>	<u>SARA</u>
Potassium Permanganate	7722-64-7	No	No	311/312	4545 Kg

<u>Ingredient</u>	<u>CAS. NO.</u>	<u>Acute</u>	<u>Chronic</u>	<u>Fire</u>	<u>Pressure</u>	<u>Reactivity</u>	<u>Pure/Liquid</u>
Potassium Permanganate	7722-64-7	Yes	Yes	Yes	No	No	Pure

<u>Ingredient</u>	<u>CAS. NO.</u>	<u>Australian Hazchem Code</u>	<u>Poison Schedule</u>	<u>WHMIS</u>
Potassium Permanganate				C, D2B



RemOx® S-F ISCO Reagent

EC- SAFETY DATA SHEET according to Regulation (EC) № 1907/2006 of the European Parliament and of the Council, of 18 December 2006 concerning REACH

Material Safety Data Sheet
Page 9 of 9

Section 16 Other Information


NIOSH	National Institute for Occupational Safety and Health
MSHA	Mine Safety and Health Administration
OSHA	Occupational Safety and Health Administration
NTP	National Toxicology Program
IARC	International Agency for Research on Cancer
PEL	Permissible Exposure Limit
C	Ceiling Exposure Limit
TLV-TWA	Threshold Limit Value-Time Weighted Average
CAS	Chemical Abstract Service
EINECS	Inventory of Existing Chemical Substances (European)

Chithambarathanu Pillai (S.O.F.)
May 2008

The information contained herein is accurate to the best of our knowledge. However, data, safety standards and government regulations are subject to change and, therefore, holders and users should satisfy themselves that they are aware of all current data and regulations relevant to their particular use of product. CARUS CORPORATION DISCLAIMS ALL LIABILITY FOR RELIANCE ON THE COMPLETENESS OR ACCURACY OR THE INFORMATION INCLUDED HEREIN. CARUS CORPORATION MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR PARTICULAR USE OR PURPOSE OF THE PRODUCT DESCRIBED HEREIN. All conditions relating to storage, handling, and use of the product are beyond the control of Carus Corporation, and shall be the sole responsibility of the holder or user of the product.

CARUS CORPORATION, 315 5TH STREET, PERU, ILLINOIS 61354
CARUS NALON S.L. IS A DIVISION OF CARUS CORPORATION, 315 5TH STREET, PERU, ILLINOIS 61354



 (Carus and Design) is a registered service mark of Carus Corporation. CARUS® is a registered trademark of Carus Corporation. RemOx® is a trademark of Carus Corporation. Responsible Care® is a registered service mark of the American Chemistry Council.