



**CARULITE<sup>®</sup> 110 TR Oxidation Catalyst**  
EC- SAFETY DATA SHEET according to Regulation (EC) №  
1907/2006 of the European Parliament and of the Council, of 18  
December 2006 concerning REACH

Material Safety Data Sheet

**Section 1 Chemical Product and Company Identification**

<b>MANUFACTURER'S NAME:</b> CARUS CORPORATION	<b>TELEPHONE NUMBER:</b> (815) 223-1500 <b>Fax:</b> (815) 224-6816 <b>Web:</b> <a href="http://www.caruscorporation.com">www.caruscorporation.com</a> <b>E-mail:</b> <a href="mailto:salesmkt@caruscorporation.com">salesmkt@caruscorporation.com</a>
<b>MANUFACTURING FACILITY:</b> Carus Corporation 1500 Eighth Street P. O. Box 1500 LaSalle, IL 61301	<b>EMERGENCY TELEPHONE NO.</b> (800) 435 - 6856 (USA) (815) 223 -1500 (other countries) <b>CHEMTREC<sup>®</sup> TELEPHONE NO.</b> (800) 424-9300 (USA)

**Section 2 Composition and Information on Ingredients**

<b>SYNONYMS:</b> None		
<b>CLASS:</b> Inorganic oxides		
<b>HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS) RATINGS:</b>		
Health Hazard	1	
Flammability Hazard	0	
Reactivity Hazard	0	
Personal Protection Index	E	
<b><u>HAZARDOUS INGREDIENTS</u></b>		
<b><u>Material</u></b>	<b><u>CAS No.*</u></b>	<b><u>Hazard Data</u></b>
Manganese Oxide	1313-13-9	<b>PEL** C**** 5 mg Mn per cubic meter of air</b> <b>TLV-TWA*** 0.2 mg Mn per cubic meter of air</b>
Copper Oxide	1317-38-0	<b>PEL** 1 mg Cu per cubic meter of air</b> <b>TLV-TWA*** 1mg Cu per cubic meter of air</b> <b>TLV-TWA*** 10 mg per cubic meter of air</b>
Lanthanide Oxides	NA	
Aluminum Oxide	1344-28-1	<b>TLV-TWA*** 10 mg per cubic meter of air</b>
* Chemical Abstract Service Number		
** OSHA Permissible Exposure Limit, manganese compounds (as Mn), copper dusts and mists (as Cu), 29 CFR 1910.1000 Table Z-1.		
*** American Conference of Governmental Hygienists, 1999. TLV-TWA = the time weighted average concentration for a normal 8-hour workday and a 40-hour work week, to which nearly all workers may be repeatedly exposed, day after day, without adverse effect.		
**** Ceiling Exposure Limit or maximum exposure concentration not to be exceeded under any circumstances.		



**CARULITE® 110 TR Oxidation Catalyst**  
EC- SAFETY DATA SHEET according to Regulation (EC) №  
1907/2006 of the European Parliament and of the Council, of 18  
December 2006 concerning REACH

Material Safety Data Sheet

### Section 3 Hazards Identification

#### EFFECTS OF ACUTE EXPOSURE

1. Eye Contact: May cause eye irritation.
2. Skin Contact: May cause skin irritation or dehydrating of skin.
3. Inhalation: May cause nose, throat and lung irritation.
4. Ingestion: Irritating to mouth, throat and stomach.

#### EFFECTS OF CHRONIC EXPOSURE

Prolonged inhalation of manganese compounds above the TLV-TWA may cause lung irritation or central nervous system disorders. The symptoms simulate Parkinson's disease.

#### CARCINOGENICITY

NTP: not listed. IARC Monographs: not listed. OSHA Regulated: not listed.

#### MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Dust or fine powder may further irritate mucous membranes or open wounds.

### Section 4 First Aid Measures

#### EMERGENCY AND FIRST AID PROCEDURES

1. Eyes  
Immediately flush eyes with large amounts of water for at least 15 minutes holding lids apart to ensure flushing of the entire surface. Seek medical attention if irritation persists.
2. Skin  
Flush contaminated areas with large amounts of water. Remove contaminated clothing. Wash clothing before reuse.
3. Inhalation  
Remove person to fresh air. If breathing is difficult, administer oxygen. Seek medical attention.
4. Ingestion  
Never give anything by mouth to an unconscious or convulsing person. If conscious, give large quantities of water. Do not induce vomiting. Seek medical attention.

### Section 5 Fire Fighting Measures

The material itself is noncombustible but may accelerate the burning of combustible material.

**FLASHPOINT** None

**FLAMMABLE OR EXPLOSIVE LIMITS** Lower: Nonflammable. Upper: Nonflammable.

**EXTINGUISHING MEDIA** Use extinguishing medium appropriate for surrounding materials.

**SPECIAL FIREFIGHTING PROCEDURES** None

**UNUSUAL FIRE AND EXPLOSION HAZARDS** Should not be heated or rubbed in contact with organic matter or other oxidizable substances. Keep away from heat and flammable materials. Potentially an oxidizer under certain conditions.



**CARULITE<sup>®</sup> 110 TR Oxidation Catalyst**  
EC- SAFETY DATA SHEET according to Regulation (EC) №  
1907/2006 of the European Parliament and of the Council, of 18  
December 2006 concerning REACH

Material Safety Data Sheet

## Section 6 Accidental Release Measures

### STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED

Clean up spills immediately by scooping Low Copper CARULITE<sup>®</sup> Catalyst into a metal drum. Deactivate by soaking with water. Cover loosely. Flush contaminated floors with abundant quantities of water into sewer, if permitted by federal, state, or local regulations.

## Section 7 Handling and Storage

Store in a cool, dry area in closed container. Segregate from easily oxidizable materials, peroxides, chlorates, and acids. Protect containers against physical damage.

## Section 8 Exposure Controls and Personal Protection

### VENTILATION REQUIREMENTS

Provide sufficient mechanical and/or local exhaust to maintain exposure levels below TLV-TWA limit for manganese.

### RESPIRATORY PROTECTION

In cases where high dust exposure may exist, the use of NIOSH-MSHA dust and mist respirator or an air-supplied respirator is advised. Engineering or administrative controls should be implemented to control dust.

### EYE PROTECTION

Primary eye protection (safety glasses or goggles).

### GLOVES

Rubber or plastic gloves should be worn.

### OTHER PROTECTIVE EQUIPMENT

Normal work clothing is sufficient.

## Section 9 Physical and Chemical Properties

<b>BOILING POINT, 760 mm Hg</b> Not applicable	<b>VAPOR PRESSURE (mm Hg)</b> Not applicable
<b>SOLUBILITY IN WATER % BY SOLUTION</b>	Insoluble
<b>BULK DENSITY</b> Approximately 0.9 g/cc	<b>PERCENT VOLATILE BY VOLUME</b> Not volatile
<b>MELTING POINT</b> Starts to decompose with evolution of oxygen at 704°C (1300°F)	
<b>APPEARANCE AND ODOR</b> Brownish to black spheres; odorless.	



**CARULITE<sup>®</sup> 110 TR Oxidation Catalyst**  
EC- SAFETY DATA SHEET according to Regulation (EC) №  
1907/2006 of the European Parliament and of the Council, of 18  
December 2006 concerning REACH

Material Safety Data Sheet

## Section 10 Stability and Reactivity

<b>STABILITY</b> Stable under normal conditions. Moisture may reduce catalytic activity.
<b>CONDITIONS TO AVOID</b> Contact with incompatible materials or heat (704°C/1300°F).
<b>INCOMPATIBLE MATERIALS</b> Contact with peroxides and chlorates may cause violent reaction under certain conditions, such as elevated temperature or friction. May ignite organic material, especially organic solvents. May initiate polymerization of monomers. May form unstable acetylides in contact with acetylene.
<b>HAZARDOUS DECOMPOSITION PRODUCTS</b> None
<b>CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION</b> Not known to polymerize.

## Section 11 Toxicological Information

Most diagnosed cases of manganese toxicity in humans have been reported following long-term exposures to airborne concentrations of manganese above the TLV-TWA. The usual form of chronic manganese toxicity involves the central nervous system.

Reports of adverse effects in humans from ingestion of manganese are rare.

## Section 12 Ecological Information

Inorganic manganese compounds have negligible vapor pressures but exist in air as suspended particulate matter, which settle under the influence of gravity.

The transport of manganese in water is influenced by the solubility of the form present. Insoluble forms, such as manganese dioxide, are transported as sediments.

The bioaccumulation of manganese in the food chain does not appear to be significant.

## Section 13 Disposal Considerations

CARULITE<sup>®</sup> 110 TR Oxidation Catalyst is not considered a hazardous waste under 40 CFR 261. Dispose of deactivated CARULITE<sup>®</sup> in a landfill approved to accept chemical waste, after verifying that it is not contaminated with hazardous substances through usage.

## Section 14 Transport Information

Proper Shipping Name:	Manganese Dioxide Compound.
ID Number:	Not regulated by Department of Transportation (DOT).
Product R.Q. (lb.)	None



**CARULITE<sup>®</sup> 110 TR Oxidation Catalyst**  
EC- SAFETY DATA SHEET according to Regulation (EC) №  
1907/2006 of the European Parliament and of the Council, of 18  
December 2006 concerning REACH

Material Safety Data Sheet

### Section 15 Regulatory Information

CARULITE<sup>®</sup> 110 TR Oxidation Catalyst contains manganese compounds (CAS Reg. No. N/A) and copper compounds (CAS Reg. No. N/A) as part of the mixture and is subject to the reporting requirements of Section 313 of Title III Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Components of this product are listed on the TSCA Inventory.

### Section 16 Other Information

MSDS Status: Revised - May 2008

Supercedes Date: March 2008

Revised By: Chithambarathanu Pillai (S.O.F.)

The information contained herein is accurate to the best of our knowledge. However, data, safety standards and government regulations are subject to change and, therefore, holders and users should satisfy themselves that they are aware of all current data and regulations relevant to their particular use of product. CARUS CORPORATION DISCLAIMS ALL LIABILITY FOR RELIANCE ON THE COMPLETENESS OR ACCURACY OR THE INFORMATION INCLUDED HEREIN. CARUS CORPORATION MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR PARTICULAR USE OR PURPOSE OF THE PRODUCT DESCRIBED HEREIN. All conditions relating to storage, handling, and use of the product are beyond the control of Carus Corporation, and shall be the sole responsibility of the holder or user of the product.

---

CARUS CORPORATION, 315 5<sup>TH</sup> STREET, PERU, ILLINOIS 61354



Responsible Care<sup>®</sup>  
Good Chemistry at Work



CARUS<sup>®</sup> Carus and Design is a registered service mark of Carus Corporation. CARULITE<sup>®</sup> is a registered trademark of Carus Corporation. CARUS<sup>®</sup> is a registered trademark of Carus Corporation. Copyright 1998. Responsible Care<sup>®</sup> and CHEMTREC<sup>®</sup> are registered service marks of the American Chemistry Council.