



# CARUS<sup>®</sup> Mn S MANGANESE SULFATE

## Material Safety Data Sheet

Page 1 of 4

### Section 1 Chemical Product and Company Identification

<b>MANUFACTURER'S NAME:</b> CARUS CORPORATION	<b>TELEPHONE NUMBER:</b> (815) 223-1500 <b>Web:</b> <a href="http://www.caruschem.com">www.caruschem.com</a>
<b>MANUFACTURING FACILITY:</b> Carus Corporation 1500 Eighth Street P. O. Box 1500 LaSalle, IL 61301	<b>EMERGENCY TELEPHONE NO.</b> (800) 435 - 6856 (USA) (815) 223 -1500 (other countries) <b>CHEMTREC<sup>®</sup> TELEPHONE NO.</b> (800) 424-9300 (USA)

### Section 2 Composition and Information on Ingredients

<b>SYNONYMS:</b> Manganese Sulfate, Monohydrate Manganese Sulfate			
<b>CLASS:</b> Inorganic salt			
<b>HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS) RATINGS:</b>			
Health Hazard	1		
Flammability Hazard	0		
Reactivity Hazard	0		
Personal Protection Index	E (Safety Glasses, Gloves, and Dust Respirator)		
<b>HAZARDOUS INGREDIENTS:</b>			
<u>Material or Component</u>	<u>CAS No.*</u>	<u>%</u>	<u>Hazard Data</u>
Manganese sulfate monohydrate	10034-96-5	33	<b>PEL** C****</b> 5 mg Mn per cubic meter of air <b>TLV-TWA***</b> 0.2 mg Mn per cubic meter of air <b>IDLH*****</b> 500 mg Mn per cubic meter of air
* Chemical Abstract Service Number			
** OSHA Permissible Exposure Limit, manganese compounds (as Mn), 29 CFR 1910.1000 Table Z-1.			
*** American Conference of Governmental Hygienists, 1999. TLV-TWA = the time weighted average concentration for a normal 8-hour workday and a 40-hour work week, to which nearly all workers may be repeatedly exposed, day after day, without adverse effect.			
**** Ceiling Exposure Limit or maximum exposure concentration not to be exceeded under any circumstances.			
***** Immediately dangerous to life and health concentration (IDLH) is taken from NIOSH (National Institute of Occupational Safety and Health) pocket guide to chemical hazards, Feb 2004 edition.			

### Section 3 Health Hazard Data

<b>EFFECTS OF ACUTE EXPOSURE</b>
1. Eye Contact May cause eye irritation.
2. Skin Contact May cause skin irritation.
3. Inhalation May cause irritation of nasal passages. Additional effects may include shortness of breath and asthma.
4. Ingestion May cause abdominal pain and nausea.



# CARUS<sup>®</sup> Mn S MANGANESE SULFATE

## Material Safety Data Sheet

Page 2 of 4

### EFFECTS OF CHRONIC EXPOSURE

Prolonged inhalation of manganese compounds above the TLV-TWA may cause lung irritation or central nervous system disorders. The symptoms simulate Parkinson's disease.

### CARCINOGENICITY

NTP: No IARC Monographs: No OSHA Regulated: No

### MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Exposure to mists may further irritate mucous membranes or open wounds.

## Section 4 First Aid Measures

### EMERGENCY AND FIRST AID PROCEDURES

1. Eyes  
Immediately flush eyes with large amounts of water for at least 15 minutes holding lids apart to ensure flushing of the entire surface. Seek medical attention if irritation persists.
2. Skin  
Flush contaminated areas with large amounts of water for at least 15 minutes. Remove contaminated clothing. Wash clothing before reuse.
3. Inhalation  
Remove person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, administer oxygen. Seek medical attention.
4. Ingestion  
Never give anything by mouth to an unconscious or convulsing person. Seek medical attention.

## Section 5 Fire Fighting Measures

**FLASHPOINT** None

**FLAMMABLE OR EXPLOSIVE LIMITS** Lower: Nonflammable Upper: Nonflammable

**EXTINGUISHING MEDIA** Use extinguishing medium appropriate for surrounding materials.

**SPECIAL FIREFIGHTING PROCEDURES** In the event of a fire avoid breathing vapors or dust, may use an appropriate breathing apparatus. Dike area to prevent run off and contamination of water sources, if possible.

**UNUSUAL FIRE AND EXPLOSION HAZARDS** Keep away from strong oxidizers.

## Section 6 Accidental Release Measures

### STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED

Ventilate area of leak or spill. Contain spills by diking. Absorb spills using adsorbent clay and transfer into a suitable container for reclamation or disposal. Flush contaminated floors with abundant quantities of water into sewer, if permitted by federal, state, or local regulations.

## Section 7 Handling and Storage

Store in a cool, ventilated area in closed container. Segregate from permanganates, other oxidizing agents, peroxides, and chlorates. Protect containers against physical damage.

## Section 8 Exposure Controls and Personal Protection

### VENTILATION REQUIREMENTS

Provide sufficient mechanical and/or local exhaust to maintain exposure levels below TLV-TWA limit for Mn.

### RESPIRATORY PROTECTION



# CARUS<sup>®</sup> Mn S MANGANESE SULFATE

## Material Safety Data Sheet

Page 3 of 4

In cases where high dust exposure may exist, the use of NIOSH-MSHA dust and mist respirator or an air-supplied respirator is advised. Engineering or administrative controls should be implemented to control dust.

### EYE PROTECTION

Primary eye protection (safety glasses or goggles).

### GLOVES

Rubber or plastic gloves should be worn.

### OTHER PROTECTIVE EQUIPMENT

Normal work clothing is sufficient.

## Section 9 Physical and Chemical Properties

<b>BOILING POINT</b> >100°C	<b>VAPOR PRESSURE (mm Hg)</b> Not applicable
<b>SOLUBILITY IN WATER</b>	Soluble in all proportions
<b>VAPOR DENSITY</b> Not applicable	<b>PERCENT VOLATILE BY VOLUME</b> Not volatile
<b>MELTING POINT</b> Not applicable	
<b>APPEARANCE AND ODOR</b> Clear solution, odorless	

## Section 10 Stability and Reactivity

<b>STABILITY</b> Stable under normal conditions.
<b>CONDITIONS TO AVOID</b> Contact with incompatible materials.
<b>INCOMPATIBLE MATERIALS</b> Powdered metals and strong oxidizers.
<b>HAZARDOUS DECOMPOSITION PRODUCTS</b> Oxides of sulfur and the contained metal.
<b>CONDITIONS' CONTRIBUTING TO HAZARDOUS POLYMERIZATION</b> Material is not known to polymerize.

## Section 11 Toxicological Information

Most diagnosed cases of manganese toxicity in humans have been reported following long-term exposures to airborne concentrations of manganese above the TLV-TWA. The usual form of chronic manganese toxicity involves the central nervous system.

Reports of adverse effects in humans from ingestion of manganese are rare.

## Section 12 Ecological Information

Inorganic manganese compounds have negligible vapor pressures but exist in air as suspended particulate matter, which settle under the influence of gravity.

The transport of manganese in water is influenced by the solubility of the form present. Insoluble forms, such as manganese dioxide, are transported as sediments.

The bioaccumulation of manganese in the food chain does not appear to be significant.

## Section 13 Disposal Considerations

Dispose of container and unused contents in accordance with federal, state and local requirements.



# CARUS<sup>®</sup> Mn S MANGANESE SULFATE

## Material Safety Data Sheet

Page 4 of 4

### Section 14 Transport Information

Proper Shipping Name: Manganese Compound
ID Number: Not regulated by DOT
Product R.Q. (lb.) None

### Section 15 Regulatory Information

Carus Mn S Manganese Sulfate contains 30 % manganese compounds (CAS Reg. No. N/A) as part of the mixture and is subject to the reporting requirements of Section 313 of Title III Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.  
Components of this product are listed on the TSCA Inventory.

### Section 16 Other Information

MSDS Status:
Revised Date: December 2007
Revised By: Chithambarathanu Pillai (S.O.F.)

**The information contained herein is accurate to the best of our knowledge. However, data, safety standards and government regulations are subject to change and, therefore, holders and users should satisfy themselves that they are aware of all current data and regulations relevant to their particular use of product. CARUS CORPORATION DISCLAIMS ALL LIABILITY FOR RELIANCE ON THE COMPLETENESS OR ACCURACY OR THE INFORMATION INCLUDED HEREIN. CARUS CORPORATION MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR PARTICULAR USE OR PURPOSE OF THE PRODUCT DESCRIBED HEREIN. All conditions relating to storage, handling, and use of the product are beyond the control of Carus Corporation, and shall be the sole responsibility of the holder or user of the product.**

---

CARUS CORPORATION, 315 5<sup>TH</sup> STREET, PERU, ILLINOIS 61354



**Responsible Care<sup>®</sup>**  
Good Chemistry at Work



Carus and Design is a registered service mark of Carus Corporation. CARUS<sup>®</sup> is a registered trademark of Carus Corporation. Copyright 1998. Responsible Care<sup>®</sup> and CHEMTREC<sup>®</sup> are registered service marks of the American Chemistry Council.